

Premium LED Leuchtrahmen

Premium LED Illuminated Frames

LED-Leuchtrahmen erfüllen einen wesentlichen Zweck: Die gleichmäßige Ausleuchtung der eingelegten Backlit Folien. Das Standardprogramm von Consystec umfasst Leuchtrahmen mit 25 mm breiten, silber eloxierten Aluminium-Klappprofilen (35 mm Breite bei den Outdoor-Varianten). Auch hier wird ausschließlich Premium Qualität angeboten mit hochwertigen LED's, die die Fläche homogen ausleuchten. Auf Anfrage fertigen wir gerne auch Sonderausführungen.

LED frames fulfill one essential purpose: even illumination of the inserted backlit foils. The standard program of Consystec includes LED frames with 25 mm wide, silver anodized aluminum snap profiles (46 mm width in the outdoor versions). Again, only premium quality is offered with high-quality LEDs, which illuminate the surface homogeneously. On request we also produce customized designs.



LED Leuchtrahmen ein-/doppelseitig


LED Illuminated Frames single-/double-sided



Art.-Nr. Einseitig	Art.-Nr. Doppelseitig	Format
Art. No. Single-sided	Art. No. Double-sided	Format
LFR.250.A4	LFR.251.A4	A4
LFR.250.A3	LFR.251.A3	A3
LFR.250.A2	LFR.251.A2	A2
LFR.250.A1	LFR.251.A1	A1
LFR.250.A0	LFR.251.A0	A0
LFR.250.B3	LFR.251.B3	B3
LFR.250.B2	LFR.251.B2	B2
LFR.250.B1	LFR.251.B1	B1
LFR.250.B0	LFR.251.B0	B0

LED Leuchtrahmen einseitig, outdoor, abschließbar

LED Illuminated Frames single-sided, outdoor, lockable



Art.-Nr. Einseitig	Art.-Nr. Doppelseitig	Format
Art. No. Single-sided	Art. No. Double-sided	Format
LFR.350.A4	-	A4
LFR.350.A3	-	A3
LFR.350.A2	-	A2
LFR.350.A1	-	A1
LFR.350.A0	-	A0
LFR.350.B3	-	B3
LFR.350.B2	-	B2
LFR.350.B1	-	B1
LFR.350.B0	-	B0
LFR.350.S1	-	1000 x 2000 mm
LFR.350.S2	-	1189 x 1750 mm